



# Diesel Fuel Tank Anti-Siphons

A simple and economic way to prevent fuel theft

Specifications for determining Anti-Siphon installs:

P/N	Application Use	ID	Length
FTA-3-7	Volvo, Mack, International with 3" Fill Neck	3.00"	7.0"
FTA-25-675	Volvo, Mack, International with 2.5" Fill Neck	2.50"	6.75"
FTA-25-95	Kenworth with 2.5" Fill Neck	2.50"	9.5"
FTA-225-95	Freightliner with 2.25" Fill Neck	2.25"	9.5"
FTA-187-75	Reefer & Medium-Duty International 1.875" Fill Neck (Fits 1 7/8")	1.875"	7.5"
FTA-2-7	2" Medium-Duty Fill Neck and M2 series Freightliner	2.0"	7.0"

## Installs in less than 10 seconds



P/N FTA-3-7



P/N FTA-25-675



P/N FTA-25-95



P/N FTA-225-95



P/N FTA-187-75



P/N FTA-2-7

- Prevents diesel fuel theft and cannot be broken out by thieves
- Installation guaranteed for the life of the fuel tank
- Does not restrict fueling and there is no splash-back
- Less expensive than locking fuel caps (No keys to lose!)

**PROTECT YOUR FUEL!**  
[www.e-pdc.com](http://www.e-pdc.com)